


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 7205  
 Rec. May 29 1963  
 Well No. \_\_\_\_\_  
 Permit No. 19637  
*Do not fill in*

Owner F. Bennett Smith Driller Wolgammatt & Son

Address Winnemucca, Nevada Address P.O. Box 1026 Winne, Lic. No. 292

Location of well: NE 1/4 SW 1/4 Sec 3, T41 N/S, R. 37E, in Humboldt County

Water will be used for Irrigation & Domestic Total depth of well 600 ft.

Size of drilled hole 16 inch Weight of casing per linear foot 33 lb

Thickness of casing 3/16 Temp. of water \_\_\_\_\_

Diameter and length of casing 16 1/2 O.D. X 199  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 80 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 27, 1962 Date of completion of well March 14, 1963

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	1	1	Top Soil	
1	2	1	Gravel & Sand	
2	14	12	Yellow Clay	
14	143	129	Rocky Clay	
143	156	13	Sand & Gravel	
156	600	444	Rocky Clay with small streaks of sand & gravel 1 ft, in thickness to 6 ft. Hard to tell exact depth of each streak as to the formation	Chief aquifer (water-bearing formation) from <u>143</u> to <u>600</u> ft. Other aquifers _____
				First water at <u>143</u> feet.
				Casing perforated from <u>150</u> to <u>199</u> ft.
				Size of perforations <u>1/2X4 Mills</u>

