20504

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7280
Rec. July 15 1963
Well No.
Permit No. 20504
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Marilyn Honig c/o Nye County Develop Driller B & B Drilling Co Inc

Address Tathrop Wells, Nevada Address Beaver Utah Lic. No. 193

Location of well: NW 1/4 SW 1/4 S 1/2 Sec. 34, T. 16 N/S, R. 49 E, in Nye County, Nevada County

or 20504, 22136, 25870, 27958, 30884, 40537

Water will be used for Irrigation Total depth of well 372 ft

Size of drilled hole 26 1/2 Weight of casing per linear foot 42 lbs

Thickness of casing 1/4" Temp. of water 68°

Diameter and length of casing 14" at 372 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 71 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well March 14th 63 Date of completion of well March 30, 1963

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Surface
2	17	15	Sandy Clay
17	34	17	Sand & Gravel
34	56	22	Sandy Clay
56	67	13	Sand & Gravel
67	74	07	Gravel & Clay
74	91	19	Sand & Gravel
91	99	08	Clay
99	110	11	Sand
110	130	20	Clay
130	149	19	Sand
149	151	03	Clay
151	176	25	Sand & Gravel
176	220	44	Clay with streaks of Sand
220	252	32	Sand
252	291	39	Clay with streaks of Sand & Gravel
291	300	09	Clay
300	348	48	Clay with streak of Sand & Gravel
348	360	12	Clay
360	372	12	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 110 to 372 ft.

Other aquifers

First water at 98 feet.

Casing perforated
from 160 to 372 ft.

Size of perforations
5/16 to 1/2

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

1760 gpm @ 158 feet. 81 ft. dd.
1700 gpm @ 118 feet 41 ft. dd.

1963 JUL 15 AM 9 41
OFFICE STATE ENGINEER

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed B & B Drilling Co
Well Driller

By [illegible]

License No. 193

Dated March 16, 1963

(Not to be filled in by Driller)

RECEIVED
JUL 8 - 1963
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA