Log No. 7344
Rec. Sept. 5 1963
Well No.
Permit No. 21258
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Lee Noe — Driller: F.R.Baxter, St.R.1, Box 2490,

Address: 1137 Crane Ave Reno — Address: Carson City, Nevada. — Lic. No. 322

Location of well: a portion of ~~NW¼ NW¼~~ Sec. 11, T. 15 N/S, R. 20 E, in Ormsby County ~~of~~ State of Nevada.

Water will be used for: Garage & Trailer Court — Total depth of well: 212 feet.

Size of drilled hole: 15 inches. — Weight of casing per linear foot: 9.5 lbs.

Thickness of casing: 10 gauge. — Temp. of water: normal.

Diameter and length of casing: 8" O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: ——

If nonflowing well give depth of standing water from surface: 36 feet.

If flowing well describe control works: ——
(Type and size of valve, etc.)

Date of commencement of well: July 18, 1963 — Date of completion of well: July 31, 1963.

Type of well rig: Porta-drill (1500) Rotary.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sand.
30	70	40	Sand & streaks of Clay
70	90	20	Fine water sand.
90	140	50	Fine water sand & Streaks of Clay.
140	180	40	Coarse water sand & Streaks of hard smale.
180	212	32	Coarse gravel & water sand

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
from 70' to 212' ft.

Other aquifers: none

First water at 70' feet.

Casing perforated
from 140' to 200' ft.

Size of perforations
3/16 inch.

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
3"OD.	0	200	200	
	0	50	50	Cemented by Carson Ready Mix.
	50	212	162'	Gravel packed with 3/8" washed pea gravel purchased from Carson Ready Mix. Carson City, Nev.

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Well was pumped at 25 gal. per minute for 48 hours, and then pumped at 52 gal. per minute for 3 hours, the latter test registering 30 lbs. back pressure on tank. Water standing at 36 feet pulls down to 86 feet.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed F. R. Baxter
F.R.Baxter. Well Driller

By.....

License No. 322

Dated Aug. 31, 1963

(Not to be filled in by Driller)

1963 SEP 5 AM 9 35

STATE ENGINEER