WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Basin #107

Log No. 7365
Rec. Sept. 9 1963
Well No.
Permit No. 20432
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Standard Slag Company Driller Same

Address P.O.Bx. 471, Yerington, Nevada Address Same Lic. No.

Location of well: SW ¼ SW ¼ Sec. 31, T. 14 N/S, R. 24 E, in Douglas County

or

Water will be used for Milling Total depth of well 90

Size of drilled hole 7 3/8" Weight of casing per linear foot 0.83#5#

Thickness of casing 0.1345# Temp. of water 52°

Diameter and length of casing 6" —90feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well October 20, 1960 Date of completion of well November 4, 1960

Type of well rig Reich 650 rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Coarse gravel and clay
25	60	35	Soft clayey andesite
60	90	30	Hard andesite, streaks of clay

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 25 to 60 ft.

Other aquifers

First water at 25 feet.

Casing perforated

from 15 to 90 ft.

Size of perforations

¼" x 2" slots

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6"	0	90	90	butt welded entire length

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

40 gpm

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Standard Slag Company
Well Driller

By

License No.

Dated 9/3/63, 19

(Not to be filled in by Driller)

1963 SEP 9 AM 9 47

STATE ENGINEER