

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7387  
 Rec. Sept 23 1963  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Varian Olson Driller J. W. Cunningham

Address Con. Tell Rd. + Kivett Lane Address Rt-1 Box 844 Reno. Lic. No. 242

Location of well: NW 1/4 Sec. 34, T. 18 N/S, R. 20 E, in Washoe - County  
Conner Tell Rd. + Kivett Lane - Geiger Grade

Water will be used for Domestic Total depth of well 187'

Size of drilled hole 10" 50 ft. Weight of casing per linear foot 13"

Thickness of casing 188 w/ 3/16 Temp. of water 50

Diameter and length of casing 6" x 187'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface..... 52'

If flowing well describe control works.....  
 (Type and size of valve, etc.)

Date of commencement of well 6/11/63 Date of completion of well 6/14/63

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	8	6	hard pan
8	19	11	Grovel + Balders
19	72	53	Shale -
72	82	10	Small Gravel Some water -
82	96	14	Shal hard Ribs.
96	112	16	Small Gr. water
112	122	10	Shale -
122	135	13	Gravel + sand water -

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 170 to 185 ft.

Other aquifers 96-10-112  
+ 72 to 82

---

First water at 72 feet.

Casing perforated

from 72 to 131 ft.

Size of perforations

Torch bit

