

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 7495  
 Rec. Mar. 13 1963  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Harold Bramwell Driller Meyer Drilling Co.  
 Address 212 N. Washington, Ogden, Utah Address 505 Hot Springs Rd. Cannon 209  
 Location of well: 1/4 NE 1/4 Sec 34, T. 14 N/S, R 20 E, in Douglas County  
 or 3 miles out Johnson Lane, East 1/2 mile  
 Water will be used for Domestic Total depth of well 192 Feet  
 Size of drilled hole 6 Inch Weight of casing per linear foot 13 lbs.  
 Thickness of casing .188, Temp. of water Cool  
 Diameter and length of casing 6 5/8 O D X 67 Feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not flowing  
 If nonflowing well give depth of standing water from surface 105  
 If flowing well describe control works not flowing  
(Type and size of valve, etc.)  
 Date of commencement of well May 14 - 63 Date of completion of well May 29-63  
 Type of well rig 71 Speed Star- Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	41	41	Sand
41	105	64	Decomposed Granite
105	192	87	Hard Granite

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 105 to 192 ft.  
 Other aquifers 167 & 188

First water at 105 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations



