WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7583
Rec. Jan 7 1964
Well No.
Permit No.
Do not fill in

Owner Frank Arcularis Driller Frank [illegible]

Address Box 513. Tonopah. Nev Address Gen Del Eureka Nev Lic. No 382

Location of well: ¼ ¼ Sec. 35, T. 9 N/~~S~~ R. 45 E, in 20 miles west of Nye County

or Tonopah on Highway 8A to Belmont turn of 4 mile South known as the Henry well.

Water will be used for Stock well Total depth of well 110

Size of drilled hole 6" I D. Weight of casing per linear foot 25.#

Thickness of casing 1/4. Temp. of water

Diameter and length of casing 6" I.d. 110 Feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 12-31-63 Date of completion of well 1-2-64.

Type of well rig Cable tool.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	50	50	Sand.
50	110	60	Gravel.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 110 ft.

Other aquifers Gravel.

First water at 50 feet.

2nd. water 80 feet

Casing perforated

from 90 to 110 ft.

Size of perforations

1/4 6" long.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
0	50	50	Sand.
50	110	60	Gravel

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6" I.d.	0	110	110	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. D. Hall
Well Driller

By Frank Sokol

License No. 382

Dated 1-5-, 1964

(Not to be filled in by Driller)

1964 JAN 7 AM 9 59