WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7587
Rec. Jan. 10 1964
Well No.
Permit No.
Do not fill in

Owner ~~Lawrence & Stegall Ranches, Inc.~~ Mesquite Land Co. Driller Harry Bolton

Address Montello, Nevada Address Twin Falls, Idaho Lic. No. 129

Location of well: SE ¼ NW ¼ Sec. 26, T. 40 N/S, R. 67 E, in Elko, County

or

Water will be used for Stock Total depth of well 700'

Size of drilled hole 8" Weight of casing per linear foot 13 lb.

Thickness of casing 3/16" Temp. of water

Diameter and length of casing 6 5/8" OD Dia. 601' Long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 357'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Oct. 16, 1963 Date of completion of well Oct. 20, 1963

Type of well rig Churn

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
			Old Well, Caved in to 167' From Surface Cleaned out well runn casing and pump

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 357' to ft.

Other aquifers

First water at 357' feet.

Casing perforated

from 476' to 700' ft.

Size of perforations

1/8 x 10"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8 OD	1'Above Ground	700'	701'	Starloy Drive Shoe on Bottom of Casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

8 GPM Galer Tested

Water drawed down to 540'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Bolton
Well Driller

By

License No. 129

Dated Jan 8, 1964

(Not to be filled in by Driller)

1964 JAN 10 AM 9 53

STATE ENGINEER