

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7665  
 Rec. Mar. 3, 1964  
 Well No. 19272  
 Permit No. 21828  
 Do not fill in.

Owner Clco Anderson Driller DAE McNinch  
 Address Tulare, South Dakota Address Winnemucca, Nevada Lic. No. 219  
 Location of well: SE 1/4 SW 1/4 Sec 1, T 24 N/S, R 40 E, in Lander County  
 or \_\_\_\_\_  
 Water will be used for irrigation Total depth of well 268'  
 Size of drilled hole 17" Weight of casing per linear foot 30 #  
 Thickness of casing 10 ga. gal well Temp. of water cold  
 Diameter and length of casing 16 1/2 x 208 14" 205 268  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 76'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well Aug. 30, 1963 Date of completion of well Nov. 15, 1963  
 Type of well rig # 50 Keystone Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0	9	9	Sandy clay topsoil	
9	41	32	Clay and gravel	
41	64	23	Loose dry broken gravel	
64	87	23	Sticky brown clay	Chief aquifer (water-bearing formation) from <u>125</u> to <u>204</u> ft.
87	108	21	Loose clean gravel	
108	125	17	Sticky clay	
125	204	79	Loose clean gravel	Other aquifers <u>208- 268</u> <u>87 - 108</u>
204	208	4	Sticky clay	
208	268	60	Very loose clean gravel	
				First water at <u>87</u> feet.
				Casing perforated from <u>87</u> to <u>268</u> ft.
				Size of perforations <u>1/2 x 3/8" slots</u> <u>approx. 25 per. ft</u>

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

✓ Log No. 7665  
 Rec. Mar. 3 1964  
 Well No. 9272  
 Permit No. 21828  
 Do not fill in.

Owner Clco Anderson Driller DW McMinch

Address Tulare, South Dakota Address Winnemucca, Nevada Lic. No. 219

Location of well: SE 1/4 SW 1/4 Sec. 1, T. 24 N/S, R. 40 E, in Lander County

Water will be used for irrigation Total depth of well 268'

Size of drilled hole 17" Weight of casing per linear foot 30 #

Thickness of casing 10 ga. gal well Temp. of water cold

Diameter and length of casing 16 1/2 x 208 14" 208 268  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 76'

If flowing well describe control works.....  
(Type and size of valve, etc.)

Date of commencement of well Aug. 30, 1963 Date of completion of well Nov. 15, 1963

Type of well rig # 50 Keystone Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	Sandy clay topsoil
9	41	32	Clay and gravel
41	64	23	Loose dry broken gravel
64	87	23	Sticky brown clay
87	108	21	Loose clean gravel
108	125	17	Sticky clay
125	204	79	Loose clean gravel
204	208	4	Sticky clay
208	268	60	Very loose clean gravel

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 125 to 204 ft.

Other aquifers 208- 268  
87 - 108

First water at 87 feet.

Casing perforated  
 from 87 to 268 ft.

Size of perforations  
1/2 x 2" slots  
approx. 25 per. ft

