

# two well  
21043

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7687  
 Rec. Mar. 9 1964  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Frank Mayhew Driller Frank Schuh

Address Box 513, Tonopah Nev Address San Del Eureka Nev Lic. No. 382

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec 33, T. 6 N/8, R. 44 E, in Yucca County  
 or \_\_\_\_\_

Water will be used for Stock water Total depth of well 110

Size of drilled hole 8 Weight of casing per linear foot 25

Thickness of casing 3/8 Temp. of water Not tested water Cold.

Diameter and length of casing 6 in I.d. 110 feet in hole.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure not flowing.

If nonflowing well give depth of standing water from surface 40 feet from surface.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 12-31-63 Date of completion of well 1-2-64

Type of well rig Cable tool.

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	50	50	Sand.
50	110	60	Gravel.

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from about 50 to 110 ft.

Other aquifers \_\_\_\_\_  
2nd water at 80 feet in gravel.

---

First water at 50 feet.

---

Casing perforated  
 from 90 to 110 ft.  
1/4" wide 6 in long.

Size of perforations \_\_\_\_\_  
20 perforating to a 20 foot joint.

