

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7724
 Rec. Mar 13 1964
 Well No. _____
 Permit No. 21860
 Do not fill in.

Owner Harry J. Frost Driller John Champion
 Address Huffaker Lane, Reno, Nevada Address 6390 S. Virginia, Reno, Nev. Lic. No. 29
 Location of well: SE 1/4 SE 1/4 Sec. 2, T. 18 N/S, R. 19 E, in Washoe County
 or _____
 Water will be used for Domestic and Stockwatering Total depth of well 169' - 6"
 Size of drilled hole 7 1/2" Weight of casing per linear foot 19.45#
 Thickness of casing .280" Temp. of water Cold - approx. 60° F.
 Diameter and length of casing 170' - 6.065" I.D. STD T&C
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure approx. 10 gpm - pressure approx. 5 psi
 If nonflowing well give depth of standing water from surface -
 If flowing well describe control works none - was used for stock water only when drilled.
(Type and size of valve, etc.)
 Date of commencement of well 6/4/49 Date of completion of well 6/10/49
 Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	34	34	Sticky brown clay
34	102	68	Brown clay
102	131	29	Brown clay
131	132	1	Fine sand
132	143	11	Clay
143	144	1	Fine sand
144	147	3	Brown clay
147	149	2	Fine sand
149	154	5	Red sandy clay
154	158	4	Fine sand
158	169	11	Blue, red, and black sand

Water-bearing Formation, Casing Perforations, etc.
 Bottom 40'
 Chief aquifer (water-bearing formation) approx.
 from 131' to 170' ft.
 Other aquifers _____
None significant

 First water at 33' feet.
 Casing perforated
 from 130' to 170' ft.
 Size of perforations
1/8" x 4" torch cuts

