

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 777A
 Rec. April 29 1964
 Well No. _____
 Permit No. _____

Do not fill in

Owner Ward S Bowden Driller John Anderson
 Address Hawthorne Nev Address 64 E 4th St Sparks Nev Lic. No. 307
 Location of well: NW 1/4 SE 1/4 Sec 30, T17N/S, R20E, in _____ County
 or Lot 6 Block F New Washed Sub 2 City of Washoe ARW 050-296-06
 Water will be used for Domestic Total depth of well 151'
 Size of drilled hole 6" Weight of casing per linear foot 13 lbs.
 Thickness of casing 1.88 or 3/16 Temp. of water Cool
 Diameter and length of casing 6" 130'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 50'
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well March 23-64 Date of completion of well April 15-64
 Type of well rig Art. Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Loose Sand
5	50	45'	Brown Sandy Clay
50	70	20	Fine brown Sand
70	85	15	Sand + Gravel
85	125	40	Sandy clay
125	130	5	Gravel
130	151	21	Sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 125 to 130 ft.

Other aquifers 70-85'

First water at 50 feet.

Casing perforated from 120 to 130 ft.

Size of perforations 1/8 x 4" torch cut



