

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

✓ Log No. 7793  
 Rec. May 8 1964  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Colonel Fletcher Driller A. & B. Contractors

Address Topaz Lake, Nevada Address Sun Valley, Nevada Lic. No. 287

Location of well: NE 1/4 NW 1/4 Sec 31, T. 10. N/6, R. 22 E, in Douglas County

or \_\_\_\_\_

Water will be used for domestic Total depth of well 80'

Size of drilled hole 6" Weight of casing per linear foot 12 lbs.

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6" X 80'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 24'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 10-7-63 Date of completion of well 10-10-63

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	80	80	clay & rock

#### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 50 to 80 ft.

Other aquifers \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

First water at 50 feet.

Casing perforated  
 from 50 to 80 ft.

Size of perforations  
1/8 X 6"

