

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7802  
 Rec. May 8 1964  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Do not fill in.

Owner Ed Gillespie Driller A & B Contractors

Address P.O. Box 95, Black Spgs., Nev. Address Sun Valley, Nev. Lic. No. 287

Location of well: S.E. 1/4 S.E. 1/4 Sec. 16, T. 19 N/S, R. 19 E, in Washoe County  
 or \_\_\_\_\_

Water will be used for domestic Total depth of well 80'

Size of drilled hole 6-5/8" Weight of casing per linear foot 13#

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6-5/8" X 80'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 30'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 6-25-63 Date of completion of well 7-1-63

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	Rocky top soil
7	35	28	rocky clay
35	45	10	rock & sand
45	65	20	sandy clay
65	80	15	coarse sand

#### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 65 to 80 ft.

Other aquifers \_\_\_\_\_

First water at 18' feet.

Casing perforated

from 60 to 80 ft.

Size of perforations

1/8 X 6"

