

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

X Log No. 7816
 Rec. May 8 1964
 Well No.
 Permit No.
 Do not fill in.

Owner George Smith Driller A & B Contractors
 Address W. 4th Ave, Sun Valley, Nev. Address Sun Valley, Nev. Lic. No. 287
 Location of well: SE 1/4 SW 1/4 Sec. 18, T. 20 N/8, R. 22 E, in Washoe County
 of
 Water will be used for domestic Total depth of well 110'
 Size of drilled hole 6-5/8" Weight of casing per linear foot 13#
 Thickness of casing 188 ga. Temp. of water cold
 Diameter and length of casing 6-5/8" X 110'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 42'
 If flowing well describe control works
(Type and size of valve, etc.)
 Date of commencement of well 6-4-63 Date of completion of well 6-10-63
 Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Top soil
10	90	80	sandy clay
90	110	20	coarse sand & clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 90 to 110 ft.

Other aquifers.....

First water at 82 feet.

Casing perforated
 from 70 to 110 ft.

Size of perforations
1/8 X 6"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6-5/8"	1	0	110	188 ga; welded joints; no drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

10 GPM; 30' DD; bail test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A. B. Contractors
Well Driller

By M. [Signature]

License No. 287

Dated April 16, 1964

(Not to be filled in by Driller)
