WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7959
Rec. June 30 1965
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Mrs Lee Chevalley Driller J W Cunningham

Address Home Garden Dr. Reno Nev Address Reno Nevada Lic. No. 242

Location of well NE ¼ SE ¼ Sec. 34, T. 18 N/S, R. 20 E, in Washoe County

or

Water will be used for Domestic Total depth of well 203'

Size of drilled hole 6" Weight of casing per linear foot 13

Thickness of casing 3/16 Temp. of water 47°

Diameter and length of casing 6" X 203'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 110'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4/7/64 Date of completion of well 4/25/64

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	8	6	hard Pum + Balders
8	21	13	Gravel + Balders
21	95	74	Brown Shale
95	115	20	hard Rock Brown
115	136	21	Loose Shale Some water
136	172	36	hard Shale Brown
172	185	13	hard Grey Shale
185	200	15	Small Gravel - water
200	203	3	hard Rock

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 185 to 200 ft.

Other aquifers 115 - 136

First water at 115 feet.

Casing perforated

from 115 to 200 ft.

Size of perforations

Torch Cut Large

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
				Grouted Clay + Cement.

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Bailer Test Est. approx 15 to 20 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. W. Cunningham
Well Driller

By

License No. 6224

Dated 5/1/6, 1964

(Not to be filled in by Driller)