

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7996  
 Rec. July 21 1964  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner C. W. Zunder Driller Pete Anderson  
 Address 16550 Pyramid Lake Rd. (S) Address 604 E 4th St Reno, Nev. Lic. No. 307  
 Location of well NE 1/4 Sec. 6, T. 16 N, R. 20 E, in Washoe County  
 or Lot 11, Block N1 Washoe Valley Farms  
 Water will be used for Domestic Total depth of well 70'  
 Size of drilled hole 6" Weight of casing per linear foot 13 lbs.  
 Thickness of casing 1.88 or 3/16" Temp. of water Cool  
 Diameter and length of casing 6" 70'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 22'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well June 26-64 Date of completion of well June 28-64  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	loose soil
2	8		hard soil
8	25		Course sand
25	30		Blue clay
30	45		sand + gravel
45	55		Brown clay
55	68		sand + coarse gravel
68	70		loose sand & gravel

**Water-bearing Formation, Casing Perforations, etc.**

Chief aquifer (water-bearing formation)  
 from 68 to 70 ft.

Other aquifers \_\_\_\_\_

First water at 25 feet.

Casing perforated  
 from 60 to 70 ft.

Size of perforations  
1/8" x 4"

