

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8073¹⁷⁹
 Rec. Nov. 13, 1964
 Well No.
 Permit No.
 Do not fill in.

Owner John Kelling Driller Reno Pump & Supply
 Address Address 7168 So. Virginia - Reno Lic. No. 285
 Location of well: N 1/4 SE 1/4 Sec. 31, T. 17N/S, R. 20E, in Washoe County
 or Washoe Valley
 Water will be used for Domestic Total depth of well 200'
 Size of drilled hole 6" Weight of casing per linear foot
 Thickness of casing 1.80" A53 Prime Temp. of water Cold
 Diameter and length of casing 6" x 200'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 35'
 If flowing well describe control works
(Type and size of valve, etc.)
 Date of commencement of well October 22, 1964 Date of completion of well November 6, 1964
 Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	13	13	Sand
13	36	23	Iron Oxide Sand
36	40	4	Gray Sand and Silt W/B
40	88	48	Blue Sandy Clay
88	90	2	Stratified Layers of Sand and Clay
90	105	15	Sand and Green Clay
105	112	7	Sand
112	160	48	Brown Silty Clay
160	165	5	Gravel and Sand W/B
165	193	28	Blue Clay and Gravel
193	195	2	Sand and Gravel W/B
195	200	5	Sand and Silt W/B

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 160 to 200 ft.

Other aquifers.....

See Log.

First water at 20 feet.

Casing perforated

from 184 to 199 ft.

Size of perforations

1/16" x 4" Torch cut

