

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 188
 Rec. Nov. 13 1964
 Well No. _____
 Permit No. _____
Do not fill in

Owner Major Vernon D. Boyd Driller Reno Pump & Supply

Address Steamboat, Nevada Address 7468 So. Virginia-Reno Lic. No. 285

Location of well: S 1/4 NE 1/4 Sec. 33, T. 18 N/S, R. 20 E, in Washoe County

Water will be used for Domestic Total depth of well 56'

Size of drilled hole 6" Weight of casing per linear foot _____

Thickness of casing 10 Ga. Temp. of water Cold

Diameter and length of casing 6" x 56'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 19'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 2/27/62 Date of completion of well 3/1/62

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Black topsoil
5	34	29	Sandy yellow clay w/ 1/2" gravels
34	50	16	Coarse sand & fine gravels
50	56	6	Coarse sand & fine gravels w/ 60% silt

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 34 to 56 ft.

Other aquifers _____

Very clean water

First water at 19 feet.

Casing perforated
 from 32 to 52 ft.

Size of perforations
1/8" x 1 1/2"

Factory



