

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8283  
 Rec. Jan 5 1965  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Silver State Realty Driller A & B Contractors  
 Address Reno Nevada Address Sun Valley Nevada Lic. No. 287  
 Location of well: SE 1/4 NW 1/4 Sec 31, T. 16 N/S, R. 22 E, in Washoe County  
 or Block H Lot 25 New Washoe Sub.

Water will be used for Domestic Total depth of well 110  
 Size of drilled hole 8" Weight of casing per linear foot 13#  
 Thickness of casing 188 Wall Temp. of water cold  
 Diameter and length of casing 6 5/8" x 90'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface..... 35'  
 If flowing well describe control works.....  
(Type and size of valve, etc.)

Date of commencement of well Sept. 10 1964 Date of completion of well Sept. 18 1964  
 Type of well rig Cable Tool

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	5	5	Sandy Top Soil	
5	45	40	Sandy Clay	Chief aquifer (water-bearing formation)
45	68	23	Sand	from <u>45</u> to <u>68</u> ft.
68	98	30	Tight Sandy Clay	Other aquifers.....
98	110	12	Grey Granite	.....
				First water at <u>45</u> feet.
				Casing perforated
				from <u>65</u> to <u>85</u> ft.
				Size of perforations
				<u>1/8</u> x <u>6"</u>



