SAME AS #1297

Log No. 8296
Rec. Nov 6 1964
Well No.
Permit No. 22361
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Reno Live Stock Sale Yard

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Helen V. Hawkins Driller: J. C. Faretto & Son

Address: 2985 Mill St, Reno, Nev Address: 736 Humboldt St, Reno Lic. No. 2

Location of well: ~~NE~~ ¼ ~~NW~~ ¼ Sec. 18, T. 19 N/~~S~~, R. 20 E, in Truckee Meadows, Washoe County

or about 1½ miles east from the County Hospital on Mill Street

Water will be used for: Domestic & stock Total depth of well: 47'-08"

Size of drilled hole: 6 inch Weight of casing per linear foot: 19.18 Lbs

Thickness of casing: .280 of an inch Temp. of water: 56°

Diameter and length of casing: 6" inside diam. 11'-03" to 11'-08" lengths

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 12 inches

If flowing well describe control works:

(Type and size of valve, etc.)

Date of commencement of well: May 9, 1950 Date of completion of well: May 12, 1950

Type of well rig: Cable Tool Rig. Keystone Type Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Bolders & rocks with yellow clay soil.
3	11	8	1st water. Water level 3 ft. Bolders & rocks with clay soil. Loose.
11	17	6	2nd water. Water. Bolders & rocks with coarse sand, gravel. Loose.
17	26	9	3rd. water. Water. Bolders & rocks with medium to coarse sand, gravel & stones. Loose.
26	32	6	4th water. Little water. Bolders & rocks with medium to coarse sand, gravel + stones with clay soil. Loose.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 11 to 17 ft.

Other aquifers: 17 to 26

40 to 48

32 to 40

26 to 32

First water at 3 feet.

Casing perforated

from 40 to 46 ft.

Size of perforations

3/8" x 1½"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
32	40	8	5th water. Little water. Medium to coarse sand & gravel with soil. Loose.
40	48	8	6th water. Little water. Coarse sand & gravel. Clean material. Loose.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0'-08"	47'-08"	48'-04"	Standard black pipe. 1/4"x3" electric weld couplings. Short pattern drive shoe. Perforated with a Mills Perforator.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Sand material consist of black river bottom sand. Washed in bailers with clay like soil. Pumped & cleaned with an air compressor 15 gal per minute 11'-08" drawdown.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated May 28, 19 50

This log was re-written Dec. 5, 1964.
By Harold J. Faretto

(Not to be filled in by Driller)