

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8429  
 Rec. Apr 29 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Eud Donnelly (Bill Smith) Driller Enloe drilling Co.

Address 1290 Keonitz Lane Address \_\_\_\_\_ Lic. No. \_\_\_\_\_

Location of well: NE 1/4 SE 1/4 Sec. 29, T. 15 N/S, R. 20 E, in Ormsby County

or Address 1290 Keonitz Lane

Water will be used for domestic Total depth of well 100 Ft.

Size of drilled hole 12" Weight of casing per linear foot 13 lbs.

Thickness of casing 1.38 Temp. of water cold

Diameter and length of casing 6" 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 26 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well March 17 Date of completion of well March 27, 1965

Type of well rig \_\_\_\_\_

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	14	14	sandy clay
14	26	12	sandy clay and gravel
26	46	12	clay and some gravel
46	48	2	sand and gravel
48	92	44	clay with trace of gravel
92	94	2	sand
94	100	6	clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 46 to 48 ft.

Other aquifers \_\_\_\_\_

92-94

---

First water at 26 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

1/8 x 2



