N

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 8531
Rec. 19
Well No. .....
Permit No. 20868 20868
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Mrs Lee Lizzie Blackburn Brockman Rd & Gallery Co Inc
Driller: Beaver Utah 193
Address: Jathrop Wells Nevada
Address: Hye County Nevada
Lic. No. .....
Location of well: NE NW ¼ ¼ Sec. 11, T. 17 S, R. 48 E, in Hye County
or .....

Water will be used for: Irrigation
Total depth of well: 319
Size of drilled hole: 36 1/2
Weight of casing per linear feet: 42 165
Thickness of casing: 1/4"
Temp. of water: 67
Diameter and length of casing: 14" 319 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....
If nonflowing well give depth of standing water from surface: 88 ft
If flowing well describe control works ..... (Type and size of valve, etc.)

Date of commencement of well: March 1, 1963
Date of completion of well: March 10, 1963
Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Surface
3	8	5	Sandy Clay
8	12	4	Sandy Clay Gravel
12	51	39	Boulders
51	60	9	Clay Gravel
60	68	8	Boulders
68	88	20	
88	92	4	Clay Gravel
92	95	3	Boulders
95	102	7	Clay & Gravel
102	104	2	Gravel & Boulders
104	106	2	Clay & Gravel
106	110	4	Boulders & Gravel
110	112	2	Clay & Gravel
112	129	17	Clay Gravel Wet streaks of Sand & Boulders
129	141	12	Sand & Gravel
141	148	7	Clay & Gravel
148	152	4	Boulders
152	166	14	Clay & Sand
166	168	2	Boulders Gravel & Sand
168	179	11	Clay
179	186	7	Gravel & Sand
186	215	29	Clay
215	228	13	Sand Gravel & Boulders
228	268	40	Sand Gravel & Clay
268	296	28	Sand & Gravel
296	302	6	Clay
302	400	98	Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 135 to 319 ft.

Other aquifers .....

First water at 135 feet.

Casing perforated
from 140 to 319 ft.

Size of perforations
5/16 to 1/2

919