

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

W. T. Grafton

Log No. 8561
 Rec. June 21 1965
 Well No. _____
 Permit No. _____
Do not fill in

Owner Bureau of Land Management Driller Loyd Lee Bennett (Lic. No. 416.)
 Contractors

Address Las Vegas Address 470 High St. Ely, Nev. Lic. No. 14

Location of well: $\frac{1}{4}$ $\frac{1}{4}$ Sec. 5, T. 5 N. R. 66 E., in White Pine County
 or 1/2 mile North West Pony Springs.

Water will be used for Stock Well Total depth of well 224'

Size of drilled hole 9" Weight of casing per linear foot 12 lbs.

Thickness of casing 5/16" wall Temp. of water Cold

Diameter and length of casing 8 5/8 OD. 224'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 175'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 6/7/65 Date of completion of well 6/15/65

Type of well rig 24-l Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	180'	180'	Loose Gravel with Cemented Ribs.
180'	222'	42'	Loose Sand & Gravel.
222'	224'	2'	Cemented Sand & Gravel.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 180' to 222' ft.

Other aquifers _____

First water at 180' feet.

Casing perforated

from 184' to 224' ft.

Size of perforations

3/16" x 8. 3 to the
round every 18". Torch
Perforated.



