

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2637  
 Rec. Aug 27 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner INDUSTRIAL CONSTRUCTION Driller A.O. LARGE  
 Address ELKO, NEVADA Address Box 845 ELKO Nev. Lic. No. 397  
 Location of well: N.  $\frac{1}{4}$  W.  $\frac{1}{4}$  Sec. 38, T. 38 N.  $\frac{1}{2}$ , R. 55 E, in ELKO County  
 or \_\_\_\_\_  
 Water will be used for ROAD CONSTRUCTION Total depth of well 300 FT.  
 Size of drilled hole 8 5/8 Weight of casing per linear foot 16.90  
 Thickness of casing .188 Temp. of water 52  
 Diameter and length of casing 8 1/2 300 FT.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 90 FT.  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well 6-15-65 Date of completion of well 6-25-65  
 Type of well rig KEYSTONE 51

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	130	130	BROWN CLAY
130	145	15	SAND (WATER)
145	200	55	CLAY
200	210	10	SAND (WATER)
210	260	50	CLAY
260	290	30	SAND WITH SMALL GRAVEL
290	300	10	CLAY

### Water-bearing Formation, Casing Perforations, etc.

260

Chief aquifer (water-bearing formation)

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Other aquifers 130 & 260

First water at 90 feet.

Casing perforated

from 260 to 300 ft.

Size of perforations

3/16 2 INCHS LONG

