

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8671  
 Rec. Sept. 22 1965  
 Well No. \_\_\_\_\_  
 Permit No. 20753

Do not fill in.  
29212

Owner Joseph E. Tapera Driller Raye McNinch

Address Box 481 Pampa Texas Address Winnemucca; Nevada Lic. No. 218

Location of well: SW 1/4 SE 1/4 Sec. 26, T. 25. N/4, R. 42E, in Lander County

Water will be used for Irrigation Total depth of well 210

Size of drilled hole 17" Weight of casing per linear foot 50#

Thickness of casing 10ga Temp. of water cold

Diameter and length of casing 16" to 214' 1 1/2" to 220'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 181'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Sept 1, 64 Date of completion of well Aug. 10, 1965

Type of well rig #50 Keystone cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0	4	4	gravelly topsoil	Chief aquifer (water-bearing formation)  from _____ to _____ ft.  Other aquifers _____ <u>all clean loose gravel</u>       First water at <u>154</u> feet.
4	12	8	clay and gravel	
12	48	36	loose dry gravel	
48	88	40	clay and gravel	
88	92	4	large loose rock	
92	154	62	hard clay and gravel	
154	198	44	clean loose fine gravel	
198	212	14	clay	
212	220	8	clean loose gravel	
220	232	12	hard clay	
232	310	78	clean loose gravel	
310	326	16	hard clay	
326	330	4	loose clean gravel	

Casing perforated  
 from 154 to 220 ft.  
 factory slots  
 Size of perforations  
1/2" x 1 1/2"

