

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Frank H. Van Moyer

Log No. 8737
 Rec. 19
 Well No. _____
 Permit No. 21589
Do not fill in



Owner George W. Fisher Driller H. V. Weimer

Address Indian Springs, Nevada. Address Larrop's Well, Nevada Lic. No. I7I

Location of well: 1/4 Sec. 8,9, T. N/S, R. E, in Clark County
 or Lot A, Tract 47. Sec. 8,9, T. 16S. R. 56E.

Water will be used for Domestic Total depth of well 110 feet.

Size of drilled hole 10 inch. Weight of casing per linear foot 11.58 lbs.

Thickness of casing 10 gauge. Temp. of water 70 degrees.

Diameter and length of casing 8" O. D. x 110'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 32 feet.

If flowing well describe control works: _____
(Type and size of valve, etc.)

Date of commencement of well March, 10, 1955. Date of completion of well March, 17, 1955.

Type of well rig Cable tool.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Top soil.
4	32	28	Conglomerate.
32	110	78	Cemented gravel, (with loose stratas)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 75 to 110 ft.

Other aquifers 55' to 60'

First water at 28 feet.

Casing perforated

from 50 to 110 ft.

Size of perforations

3/16" x 6"



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	110	110	Cemented from 0 to 50'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed H. V. Weimer
Well Driller

By

License No. 171

Dated March 20, 1955

(Not to be filled in by Driller)
