Log No. 8791
Rec. Jan 3, 1966
Well No.
Permit No. 22079
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Gerald Sharp Driller Gerald Sharp

Address Nyala Via Tonopah Nev Address Nyala Via Tonopah Nev. Lic. No.

Location of well SE ¼ SE ¼ Sec. 34, T. 5 N/S, R. 55 E, in Nye County

Permit No. 22079

Water will be used for Irrigation & Domestic Total depth of well 395'

Size of drilled hole 28 in Weight of casing per linear foot 50 lb.

Thickness of casing 1/4" Temp. of water 60°

Diameter and length of casing 16" 395'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure not

If nonflowing well give depth of standing water from surface 69 ft.

If flowing well describe control works not
(Type and size of valve, etc.)

Date of commencement of well Sept 21, 1965 Date of completion of well Oct. 1, 1965

Type of well rig Winter-Wiers Reverse Circulating Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	24	24	Sandy Topsoil
24	30	6	Clay
30	32	2	Clay & Gravel
32	36	4	Sand & Gravel
36	48	6	Clay
48	60	12	Clay, Sand & Gravel
60	66	6	Clay
66	80	14	Clay, Sand & Gravel
80	96	16	Sand & Gravel (Clean)
96	110	14	Clay, Sand & Gravel
110	116	6	Sand & Gravel
116	121	7	Clay & Gravel
121	130	9	Sand & Gravel
130	145	15	Clay & Gravel
145	150	5	Clay, Sand & Gravel
150	156	6	Sand & Gravel (Clean)
156	159	3	Clay
159	167	8	Sand & Gravel (Clean)
167	184	17	Clay Sand & Gravel
184	199	15	Sand & Gravel (Clean)
199	205	6	Clay
205	216	11	Sand & Gravel
216	220	4	Clay
220	229	9	Sand & Gravel
229	241	12	Clay, Sand & Gravel
241	252	11	Sand & Gravel (Cobble stone) (some 5" Diam)

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 354 to 371 ft.

Other aquifers 80-89, 110-116, 150-156, 184-199, 205-216, 220-229, 298-304, 338-349, 380-389

First water at 69 feet.

Casing perforated

from 155 to 395 ft.

Size of perforations

3/16" x 3"

16 Rows
2 Cuts Per Lineal Ft.

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
252	256	4	Sand & Gravel
256	267	11	Clay, sand & gravel
267	273	6	Sand & Gravel
273	298	25	Clay & gravel, clay, sand & Gravel
298	304	6	Sand & Gravel (very clean)
304	305	1	Clay, sand & gravel
305	307	2	Sand & Gravel
307	338	31	Clay & gravel, Clay, sand & gravel
338	349	11	Sand & Gravel - Clean & very fine
349	354	5	Clay & Gravel
354	371	17	Sand & Gravel - (very fine & [redacted])
371	373	2	Clay & Gravel
373	380	7	Cemented Gravel
380	389	9	Sand & Gravel (very fine)
389	391	2	Clay, sand & Gravel
391	395	4	Solid clay —

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
16"	0	395	395	

GENERAL INFORMATION—Pumping Test, or Boiling Test, Quality of Water, etc.

No Test Data available

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Gerald Sharp
Well Driller

By

License No.

Dated Dec. 5, 1965

(Not to be filled in by Driller)

1966 JAN 3 AM 11 23

OFFICE
STATE ENGINEER