WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 8956
Rec. May 2 1966
Well No.
Permit No. 22301
Do not fill in

Owner Van Gardner
Address Lund, Nevada

Driller Lee Bennett (Lic. No. 416) (Contractors)
Address 470 High St. Ely, Nevada Lic. No. 14

Location of well: NE ¼ NE ¼ Sec. 17, T. 12 N., R. 62 E, in White Pine County

or

Water will be used for Irrigation Total depth of well 360'

Size of drilled hole 16" Weight of casing per linear foot 40 lbs.

Thickness of casing 1/4 wall Temp. of water cold

Diameter and length of casing 16 OD. 360'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 70'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4/2/1966 Date of completion of well 4/11/1966

Type of well rig Bucyrus Erie 24-L Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	85'	85'	Dry Sand & Gravel
85'	185'	100'	Sand & Gravel
185'	360'	175'	Clay with Gravel Strata

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 85' to 360' ft.

Other aquifers

First water at 85' feet.

Casing perforated

from 85' to 360' ft.

Size of perforations

3/8"x4"-8 to the round, every 16". Perforated with Mills Knife.

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"OD	0	360'	360'	Natural Seal

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Loyd Lee Bennett
Well Driller

By Lee Bennett

License No. 416

Dated 4/21/66, 19

(Not to be filled in by Driller)

1966 MAY 2 PM 12 02

OFFICE
STATE ENGINEER