STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

I

OFFICE USE ONLY
Log No. 100459
Permit No.
Basin 149

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57970

1. OWNER Stone Cabin Company
MAILING ADDRESS 3856 SW Sam Snead Court
Redmond, OR 97756

ADDRESS AT WELL LOCATION Test Range Rd.

2. LOCATION SW ¼ NE ¼ Sec 14 T 01N N/S R 46 E
PERMIT/WAIVER No. 66947-31536 *Issued by Water Resources* Parcel No.

Latitude N 37.93809 Longitude W 116.79155
UTM E N
☐ NAD 27 ☐ NAD 83/WGS 84
Subdivision Name: *County:* Nye

3. WORKED PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Other.....

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other .....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	4	4
Cobbles and clay		4	120	116
Claystone		120	125	5
Cobbles and clay		125	160	35
Clay		160	190	30
Sandy Clay		190	203	13
Sand with clay layers		203	320	117
Sandy clay		320	430	110
Cobbles and claystone		430	435	5
Sand and clay layerd		435	480	45
Gray claystone		480	600	120
This well did not show to have enough water to construct a well so it was abandoned with 14,000 Gallons of water mixed with 350 bags of abandonite and a 20' cement cap on top.				

Date started 5/16/2006 , 20
Date completed 5/23/2006 , 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA	NA	NA	NA

8. WELL CONSTRUCTION
Depth Drilled 600 Feet Depth Cased 0 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
36	Inches	0	Feet	50	Feet
24	Inches	50	Feet	600	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
NA	NA	NA	NA	NA

Perforations:
Type of perforation N/A
Size of perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From NA feet to.. feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M P.S.I
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada Inc., dba Humboldt Drilling & Pump Company, Inc. (Contractor)
Address 4975 W. Winnemucca Blvd. (Contractor)
Winnemucca, NV 89445
Nevada contractor's license number issued by the *State Contractor's Board* 56797
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1713
Signed C. Jaynes - Office (By driller performing actual drilling on site or contractor)
Date 5/24/2006

(Rev. 12-05)

USE ADDITIONAL SHEETS IF NECESSARY