


STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT



OFFICE USE ONLY  
Log No. 101054  
Permit No. 72131  
Basin 108

Please complete this form in its entirety in accordance with NRS 534.179 and NAC 534.340

NOTICE OF INTENT NO. 56296

1. OWNER Mike Faretto ADDRESS AT WELL LOCATION  
MAILING ADDRESS 291 Osborne Lane Hwy 208 Mason Valley  
Yerington, NV 89447

2. LOCATION 1/4 SW 1/4 Sec. 14 12 N/S R 25 E Lyon County  
PERMIT NO. W581/72131 Issued By Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  New Well  Replace  Recondition  Deepen  Abandon  Other  
4. PROPOSED USE  Domestic  Irrigation  Test  Monitor  Municipal/Indus  Shock  Cable  Rotary  RVC  Air  Other

6. LITHOLOGIC LOG

Material	From	To	Thickness
Top Soil	0	1	1
Sandy Clay	1	12	11
Sand w/Gravel and Cobbles	12	175	163
Sand & Gravel, Cobbles, Little Clay	175	188	13
Coarse Sand, Gravel, Cobbles	188	190	2
Coarse Sand, Gravel, Clay	190	210	20
Coarse Sand, Gravel, Cobbles	210	224	14
Coarse Sand, Gravel, Clay	224	260	36
Coarse Sand, Gravel	260	305	45
Coarse Sand, Gravel, Clay	305	320	15
Clay w/Some Sand	320	340	20
Coarse Sand	340	348	8
Coarse Sand & Clay	348	364	16
Coarse Sand, Clay, Gravel	364	396	32
Sand & Gravel	396	424	28
Sand & Clay Layers	424	428	4
Clay w/Sand Layers	428	434	6
Sand, Gravel, Clay	434	481	47
Clay w/ Sand Layers	481	483	2
Sand & Gravel w/Clay	483	519	36
Clay & Sand	519	522	3
Sand & Gravel	522	541	19
Sand & Clay	541	560	19
Coarse Sand	560	575	15
Coarse Sand, Clay, Rock	575	590	15
Clay w/Coarse Sands	590	600	10

8. WELL CONSTRUCTION  
Depth Drilled 616 Feet Depth Cased 600 Feet

HOLE DIAMETER (BIT SIZE)

From	To
36 Inches	0 Feet
28 Inches	25 Feet
25 Inches	616 Feet

CASING SCHEDULE

Size O.D. (inches)	Weight (pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30		0.250	0	5
30		Corrugated	5	25
3"		Sch 80 Gravel Feed	+2	103
18		5/16" Blank	+2	100

Type Perforation Mill Slot Double and Triple Row  
Size Perforation 0.090  
From 100 feet to 18" Double Row 220 feet  
From 220 feet to 18" Triple Row 360 feet  
From 360 feet to 18" Double Row 600 feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
Depth of Seal 100'  
Placement Method:  Pumped  Poured  
Gravel Packed:  Yes  No  
From 100 feet to 616 feet

9. WATER LEVEL  
Static Water Level 20 feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature Cool F Quality Good

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Date Started May 17 2005  
Date Completed May 21 2005

Name Hydro Resources Nevada Inc. dba Humboldt Drilling and Pump Co.  
Address 4975 West Winnemucca Boulevard  
Winnemucca, Nevada 89445

7. WELL TEST DATA

TEST METHOD:  BAILER  PUMP  AIR LIFT

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Pumping Level 85	3000	65	7

NV Contractor's LIC# issued by the State Contractor's Board 56797  
NV Driller's LIC# issued by Div. of Water Resources, on-site driller 2177  
Signed: C. Jaynes-Office Date: 8/11/05

STANDARD TIME

2806 JAN - 4 10:10:40

13111