WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 101062
Permit No.
Basin 066

NOTICE OF INTENT NO. 55758

1. OWNER Newmont mining Corp
MAILING ADDRESS P.O Box 388 Valmy, Nv 89438
ADDRESS AT WELL LOCATION Twin Creeks mine Golconda, NV

2. LOCATION SW ¼ NE ¼ Sec. 18 T. 39 N/S R. 43 E. Humboldt County
PERMIT NO. | Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. M/O 18-10 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
30' Alluvium		0	30	30
Shale--Oxide & Sulfides, Hard rock		30	1502	
H2O encounter @	1245	5 gpm		
H2O @ TD	1500	20 gpm		
Trimmy in 2.8 yrd3 3/8 gravel from Bottom to	1098.			
Place 3/8 Hole plug in hole from 1098 to 50' - 6.8 yrds3				
Pour in 68 gal Cement Slurry 15 lb per gal				
Put Monument on well-				
Developed well with 2100 gal of water.				

Date started 9/26, 2005
Date completed 10/6, 2005

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1502 Feet Depth Cased 1500 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/8 Inches		0 Feet	1502 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
23/8		3/16	0	1500

Perforations:
Type perforation Slot
Size perforation 1/8
From 1100 feet to 1400 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1098 feet to 1502 feet

9. WATER LEVEL
Static water level N/A 1040.23 feet below land surface
Artesian flow no G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co (Contractor)
Address P.O Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed (By driller performing actual drilling on site or contractor)
Date 10/6/05

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

RECEIVED
2005 OCT 21 AM 11:36
STATE ENGINEERS OFFICE

2006 JAN 17 PM 1:17