STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

I

OFFICE USE ONLY
Log No. 101035
Permit No.
Basin 071

**PRINT OR TYPE ONLY**
**DO NOT WRITE ON BACK**

*Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 57975

1. OWNER Rawhide Estates, LLC
MAILING ADDRESS 9200 Beechcraft
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION 10605 Spur St.
Winnemucca, NV 89445
Subdivision Name: Rawhide County: Humboldt

2. LOCATION NW ¼ SE ¼ Sec 31 T 35N N/S R 38 E
PERMIT/WAIVER No. 10-626-04
Issued by Water Resources Parcel No.

Latitude N40.86316
Longitude W117.74302
UTM E N
[X] NAD 27
[ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Cobbles and Clay | | 0 | 340 | 340 |

Date started: 10-Jun, 20 06
Date completed: 12-Jun, 20 06

9. WELL CONSTRUCTION
Depth Drilled 340 Feet Depth Cased 340 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | | To | |
|---|---|---|---|---|---|
| 11 | Inches | 0 | Feet | 340 | Feet |
| | Inches | | Feet | | Feet |
| | Inches | | Feet | | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | | .188 | +2 | 280 |

Perforations:
Type of perforation Mill Slot
Size of perforation 0.09
From 280 feet to 340 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [ ] Yes [ ] No
[ ] Neat Cement to [ ] Pumped [ ] Poured
[X] Cement Grout 0 to 120 [X] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [X] Yes [ ] No 120 to 340 [X] Pumped [ ] Poured
Type:
Bentonite Chips: [ ] Yes [X] No to [ ] Pumped [ ] Poured
Type:

7. Water Level
Static water level: 170' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Air Lift | 40 | | 3 Hrs |

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada Inc dba Humboldt Drilling & Pump Co
Contractor
Address 4975 W. Winnemucca Blvd.
Contractor
Winnemucca, NV 89445
Nevada contractor's license number issued by the *State Contractor's Board* 56797
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1713
Signed C. Jaynes - Office
By driller performing actual drilling on site or contractor
Date 7/19/2006

(Rev. 05 08)

**USE ADDITIONAL SHEETS IF NECESSARY**