


STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT



office use only  
Log No. 101412  
Permit No. \_\_\_\_\_  
Basin 283

NOTICE OF INTENT NO 57040

1. OWNER Painted Rock Partners  
MAILING ADDRESS PO Box 520  
Danville, Ca 94526

ADDRESS AT WELL LOCATION #2  
Latitude N 39d 35' 05.4" WGS 84  
Longitude W 119d 21' 26.2"

2. Location NW 1/4 SW 1/4 24 Sec T20 N R23 E  
PERMIT NO. 73780/W-589 PARCEL NO. 04-041-39

Storey County  
SUBDIVISION NAME

3. WORK PERFORMED			4. PROPOSED USE			5. WELL TYPE		
<input checked="" type="checkbox"/> New Well	Replace	Recondition	Domestic	Irrigation	<input checked="" type="checkbox"/> Test	Cable	<input checked="" type="checkbox"/> Rotary	RVC
Deepen	<input checked="" type="checkbox"/> Abandon	Other	Municipal/Industrial	Monitor	Stock	<input checked="" type="checkbox"/> Air	Other	Mud

6. LITHOLOGIC LOG				
Material	Water Strata	From	To	Thick-ness
Bolder, sand and clay.		0	33	33
Rock & orange clay.		33	60	27
Rock & purple clay.		60	69	9
Rock & gray clay.		69	116	47
Rock & purple clay.		116	123	7
Rock & brown clay.		123	155	32
Hard rock		155	193	38
Rock & gray clay		193	243	50
Rock & brown clay.		243	375	132
Hard rock.		375	557	182
Rock & clay.		557	695	138
cement		0	20	20
gravel		20	580	560
60 bags hole plug		580	695	115

39.534940° N  
119.356284° W  
MAD27 ConJS

8. WELL CONSTRUCTION				
Depth Drilled	695 feet		Depth Cased	695 feet
HOLE DIAMETER (BIT SIZE)				
	From	To		
8 3/4 inches	0	695	feet	feet
9 inches			feet	feet
CASING SCHEDULE				
Size O.D.	Weight/Ft.	Wall Thickness	From	To
(Inches)	(Pounds)	(Inches)	(Feet)	(Feet)
Perforations::				
Type Perforation				
Size perforation	From	feet to	feet	
	From	feet to	feet	
	From	feet to	feet	
	From	feet to	feet	
	From	feet to	feet	
Surface Seal	<input checked="" type="checkbox"/> YES	No	Seal Type:	
Depth of Seal	20	feet	Neat Cement	
			<input checked="" type="checkbox"/> Cement Grout	
			Concrete Grout	
Gravel Packed:	Yes	No		
From	feet to	feet		

9. WATER LEVEL			
Static water level	597	feet below land surface	
Artesian flow	0	GPM	0 P.S.I.
Water Temperature	cold	Degrees F	Quality

Date started 6-8 -06  
Date completed 6-20 -06

7. WELL TEST DATA			
TEST METHOD:	Bailer	Pump	x Air Lift
G.P.M.	Draw Down (Feet Below Static)		Time (hours)

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name McKay Drilling, Inc.  
2290 Pioneer Drive  
Reno, NV 89509  
NV Contractors No. 14170  
NV Driller's Lic (on site) 2121  
Signed *Steve McKay*  
By driller performing actual drilling on site or contractor  
Date 7-15 -06

STATE ENGINEERS OFFICE

2006 SEP 22 PM 1:22

RECEIVED