


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT



OFFICE USE ONLY
Log No. 101631
Permit No. _____
Basin 034

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58599

1. OWNER Carter Gold Mine ADDRESS AT WELL LOCATION CHPZ-20
MAILING ADDRESS HC-666 Box 1250
Crescent Valley Nevada 89821 Subdivision Name: Carter Hills County: Lander

2. LOCATION NW 1/4 NE 1/4 Sec 31 T27 N3R 48 E Latitude 53385.70 NAD 27
PERMIT/WAIVER No. M/O-1420 Longitude N 4446648.52 NAD 83/WGS 84

Issued by Water Resources Parcel No. _____

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test Monitor Stock
 Municipal/Industrial

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Gravle	no	0'	200'	200'
limestone	yes	200'	910'	
Dike	yes	910'	970'	
Black limestone	no	970'	980'	
Dike	no	980'	1020'	
Black limestone	no	1020'	1060'	
Dike w/ clay	yes	1060'	1110'	
Intrusive Qtz Monzonite	no	1110'	1130'	
Green Stone	yes	1130'	1140'	
Intrusive Q.M.	no	1140'	1160'	
Dike	no	1160'	1210'	
Intrusive Q.M.	yes	1210'	1600'	

90.171918°N
116.602626°W
NAD27 Conus

Material	From	To	Thick-ness
Neat Cement	50'	0'	50'
Abandonite	480'	50'	430'
Ben Sand Grout	519'	480'	39'
1/4" Gravle	525'	519'	6'
Ben Sand Grout	1478'	525'	953'
1/4" Gravle	1600'	1478'	122'

9. WELL CONSTRUCTION

Depth Drilled 1600' Feet Depth Cased 1580' Feet

HOLE DIAMETER (BIT SIZE)

From	To	Feet	Feet
9 7/8 Inches	20'	1120'	
7 7/8 Inches	1120'	1600'	
1 1/2 Inches	0'	20'	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30 3/4		188	0'	20'
2"		SCH80 PVC	0'	1480'

Perforations:

Type of perforation Slot
Size of perforation .020

From	feet to	feet	feet
1580'	1480'		

Annular Seal: Yes No

<input checked="" type="checkbox"/> Neat Cement	0' to 50'	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Cement Grout		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Concrete Grout		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> ≥30% Bentonite Grout		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

Gravel Pack: Yes No 1600' to 1478' Pumped Poured
Type: 1/4" Gravle

Bentonite Chips: Yes No Pumped Poured

7. Water Level
Static water level: N/A feet below land surface
Artesian Flow: no G.P.M. _____ P.S.I. _____
Water Temperature: N/A °F
Quality: NA

8. WELL TEST DATA

TEST METHOD: Bailor Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
5 gal Bucket	88	N/A	1/4
		52:11	1:30

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company
Address Po Box 2748
Eiko, NV 89803
Nevada contractor's license number 0030823
issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1957

Signed [Signature]
By driller performing actual drilling on site or contractor
Date 9-21-06