WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 101945
Permit No.
Basin 207

NOTICE OF INTENT NO. 56047

1. OWNER Danny Griffith
MAILING ADDRESS Po Box 15 0015 Ely NV 89301
ADDRESS AT WELL LOCATION White River Rd. NAD 27 N 38° 55' 29.1" W 115° 05' 30.2"

2. LOCATION SW ¼ SW ¼ Sec. 2 T. 12 N/S R. 61 E. White Pine County
PERMIT NO. N/A (Issued by Water Resources) | 11-300-24 (Parcel No.) | none (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	1	
clay gravel cobble		1	3	
clay		3	7	
gravel conglomerate		7	20	
clay		20	24	
clay cobbles boulders		24	44	
clay		44	52	
clay cobbles boulders		52	62	
gravel	water	62	65	
clay cobbles boulders		65	77	
gravel	water	77	80	
clay cobbles boulders		80	95	
gravel	water	95	97	
clay cobbles boulder		97	106	
gravel	water	106	108	
clay boulders		108	110	
38.924750 °N				
115.091722 °W NAD27				

Date started Oct 16, 2006
Date completed Dec 21, 2006

RECEIVED 2007 JAN -3 AM 11:31 STATE ENGINEER'S OFFICE

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
40	2	1hr

8. WELL CONSTRUCTION
Depth Drilled 110 Feet Depth Cased 110 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 Inches		50 Feet	90 Feet
6 Inches		90 Feet	110 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.9	.188	-1	110

Perforations:
Type perforation Mill
Size perforation .8 x .25" x 6 Row
From feet to feet
From 60 feet to 80 feet
From 90 feet to 110 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 90 feet

9. WATER LEVEL
Static water level 61 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Maynard Well Drilling (Contractor)
Address Po Box 64 Lund NV 89317 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 047226
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1556
Signed Owen Maynard (By driller performing actual drilling on site or contractor)
Date Dec 28 -06

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627