WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102169
Permit No.
Basin 070

NOTICE OF INTENT NO. 46757

1. OWNER Humboldt County
MAILING ADDRESS 50 W. Fifth St.
Winnemucca NV 89445

ADDRESS AT WELL LOCATION Placer Way St.,

2. LOCATION NE ¼ SE ¼ Sec. 11 T. 35 N/S R. 37 E. Humboldt County
PERMIT NO. M/O 1427 Issued by Water Resources
County Right of Way Parcel No.
Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Tan Sand	None	0'	1'	1'
Tan Silt	None	1'	7'	6'
Light Brown Sandy Silt	None	7'	13'	6'
Light Brown Silt	None	13'	31'5"	18'5"
Light Brown Silt with Coarse Sand	None	31'5"	33	2'5"
Light Brown Silt	None	33'	38'	5'
Light Brown Silt trace Gravel	None	38	53	15'
Brown Silty Clay with Gravel	None	53	62	9'
Brown Silty Clay	66'6"	62	80	18

Northing 15,371,386
Easting 2,842,237
NAD 83
40.921212 N
117.776956 W NAD27

Date started 10-24, 20 06
Date completed 10-24, 20 06

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 80 Feet Depth Cased 60 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	80 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40	+2	60

Perforations:
Type perforation Factory Slot
Size perforation .020
From 60 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 58
Placement Method: ☒ Pumped ☐ Poured 55' - 58'
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout Bentonite Chips

Gravel Packed: ☒ Yes ☐ No
From 58 feet to 80 feet

9. WATER LEVEL
Static water level 66'6" feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature <85 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Haz-Tech Drilling Contractor
Address P.O Box 940 Meridian Contractor
ID, 83680
Nevada contractor's license number issued by the State Contractor's Board 0038018
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2246
Signed Jason Adams (By driller performing actual drilling on site or contractor)
Date 10-24-06

(Rev. 12-01)
USE ADDITIONAL SHEETS IF NECESSARY
(O)-627