Plugging

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

I

OFFICE USE ONLY
Log No. 102213
Permit No.
Basin 078

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58355

1. OWNER C-PUNCH
MAILING ADDRESS 10 McDougal St.
Lovelock, NV 89419

ADDRESS AT WELL LOCATION SAGE HEN VALLEY

2. LOCATION SE ¼ NE ¼ Sec 27 T 25N N/S R 25 E
PERMIT/WAIVER No. (Issued by Water Resources) Parcel No.

Latitude 40.01062 | UTM E | ☒ NAD 27
Longitude 119.15372 | N | ☐ NAD 83/WGS 84
Subdivision Name: County:

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other.....

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	10	10
Clay		10	35	25
Decomposed Granite		35	40	5
Sandy Clay		40	155	115
Clay		155	180	25
Red Rock		180	200	20
Clay		200	210	10
Decomposed Granite		210	230	20
Clay & Decomposed Granite		230	270	40
Granite		270	400	130
Dry Hole - Drilled & Abandoned.				
Blew Hole Dry - No Sign				
Of water. Hole was backfilled with				
Native material to 10 feet BGL and				
Capped with bentonite hole plug to.				
surface.				
plugging of well log #102175				

Date started 17-Nov , 20 06
Date completed 19-Nov , 20 06

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled Feet Depth Cased Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 /14	Inches	0	Feet	400	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
		N A		

Perforations:
Type of perforation N A
Size of perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Gravel Packed: ☐ Yes ☐ No
From feet to feet

Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M P.S.I
Water temperature °F Quality

RECEIVED 2006 NOV 22 PM 1:57 STATE ENGINEERS OFFICE

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources of Nevada, Inc. dba Humboldt Drilling & Pump (Contractor)
Address 4975 W. Winnemucca Blvd. Winnemucca, NV 89445 (Contractor)
Nevada contractor's license number issued by the *State Contractor's Board* 56797
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2099
Signed Judi Leach, Office (By driller performing actual drilling on site or contractor)
Date 11/22/06

(Rev. 12-05)

USE ADDITIONAL SHEETS IF NECESSARY