STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

OFFICE USE ONLY
Log No. 1026416
Permit No.
Basin 071

NOTICE OF INTENT NO. 24153

1. OWNER Steve Tibbals
MAILING ADDRESS 3475 E Thomas Cyn Rd
Winnemucca Nv 89445

ADDRESS AT WELL LOCATION 3475 E Thomas Cyn Rd
Subdivision Name: Mills County: Humboldt

2. LOCATION sw ¼ se ¼ Sec 12 T 35N N/S R 37 E
PERMIT/WAIVER No. 013-512-13
Issued by Water Resources Parcel No.

Latitude 7 45.660w UTM E
Longitude 40 54.941n N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil & sand		0	15	15
Gravel		15	130	115
Small gravel		130	140	10
Cobbles & gravel w/ sand		140	160	20
Fairly hard consolidated gravel		160	170	10
Better more frac		170	200	30

N 40.915683
W 117.761000 NAD83

Date started: 1-Aug , 20
Date completed: 8/31/2006 , 20

9. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	200	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	steel	.25	0	20
6.75	PVC	.35	20	200

Perforations:
Type of perforation screen
Size of perforation
From 160 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 3 to 50 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 56 to 200 ☐ Pumped ☒ Poured
Type: 3/8 minus
Bentonite Chips: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 101 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality: good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
air	35		4

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name High Desert Drilling (Contractor)
Address 4225 E Mary Way Winnemucca Nv 89445 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 62237
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2140
Signed (By driller performing actual drilling on site or contractor)
Date 9-11-06

RECEIVED
2006 DEC 15 PM 2:43
STATE ENGINEERS OFFICE

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY