STATE OF NEVADA

DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

PRINT OR TYPE ONLY

OFFICE USE ONLY
Log No. 102654
Permit No.
Basin 092A

NOTICE OF INTENT NO. 57248

1. OWNER Rob Henderson
MAILING ADDRESS P.O. Box 60571 Reno, NV. 89506

ADDRESS AT WELL LOCATION
1230 Gold stone Rd Reno, NV 89506
Subdivision Name: N/A County: Washoe

2. LOCATION SW¼NW¼ Sec30T22N/S R19E
PERMIT/WAIVER NO. N/A (Issued by Water Resources) 079-352-08 (Parcel. No.)

Latitude 39,74625 N
Longitude 119,89995 W
UTM E ____ N ____
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay		0	28	28
Brown Clay		28	73	45
Sand Stone		73	125	52
DG		125	180	55
Sand Stone	X	180	225	45
DG	X	225	290	65

Date started: 09-01, 20 06
Date completed: 09-01, 20 06

RECEIVED 2006 DEC 19 AM 10:18 STATE ENGINEER'S OFFICE

9. WELL CONSTRUCTION
Depth Drilled 290 Feet Depth Cased 290 Feet

WELL DIAMETER (HOLE SIZE)

		From		To	
12 1/4	Inches	0	Feet	20	Feet
10	Inches	20	Feet	290	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8 steel	14	.188	-1	20
6 5/8 PVC	4.07	.316	20	290

Perforations:
Type of perforation Mill Slot
Size of perforation .032
From 220 feet to 290 feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement ____ to ____ ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 60 ☐ Pumped ☒ Poured
☐ Concrete Grout ____ to ____ ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout ____ to ____ ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 60 to 290 ☐ Pumped ☐ Poured
Type: 3/8 pea
Bentonite Chips: ☐ Yes ☐ No ____ to ____ ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 125 feet below land surface
Artesian Flow: none G.P.M. none P.S.I
Water Temperature: cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx.	45	200	1 hr.

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Miller & Son's Drilling (CONTRACTOR)
Address P.O. Box 8056 (CONTRACTOR)
Reno, NV. 89507
Nevada contractor's license number issued by the State Contractor's Board 37915
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1418
Signed Bruce Miller
By driller performing actual drilling on site or contractor
Date 9-29-06

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk • (214) 340-9429 • FormsOnADisk.com