WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102712
Permit No.
Basin 230

NOTICE OF INTENT NO. 29881

1. OWNER Bob Huttquist
MAILING ADDRESS P.O. Box 177
Amargosa Valley, Nv. 89020

ADDRESS AT WELL LOCATION Lyon rd.
Amargosa Valley, Nv. 89020

2. LOCATION SE ¼ NE ¼ Sec. 11 T. 18 N OR 49 E. NYE County
PERMIT NO. Issued by Water Resources 19-501-10 Parcel No. Little Nevada Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVD
☐ Air ☒ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand & gravel		0	35	35
tan, Clay, Sand layers		35	65	30
gravel w/ sand	1st	65	~~70~~ 75	10
Sandy clay w/ limestone layers		75	145	70
Sand w/ limestone layers		145	175	30
Sand	2nd	175	185	10
tan clay w/ sand layers		185	200	15
Bottom of Well			200	

DCNR/DWR
RECEIVED
APR 24 2007
LAS VEGAS OFFICE

Date started 2/26, 2007
Date completed 3/3, 2007

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 1/4 Inches	0 Feet	200 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6		PVC	0	200
Surface Protective Casing				
8	steel	.188		7

Perforations:
Type perforation Machined
Size perforation 1/8" x 3", every 12", 4R
From 80 feet to 120 feet
From 140 feet to 160 feet
From 180 feet to 190 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 200 feet

9. WATER LEVEL
Static water level 65 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. Contractor
Address H.C. 70 Box 543 Contractor
Amargosa Valley, Nv. 89020
Nevada contractor's license number issued by the State Contractor's Board 5376-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2160
Signed [signature] By driller performing actual drilling on site or contractor
Date 3/23/07

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 12-01) 070-627