STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102805
Permit No.
Basin 107

NOTICE OF INTENT NO. 59023

1. OWNER MAXINE GROSO
MAILING ADDRESS P. O. BOX 281384
LAMOILLE, NV 89828

ADDRESS AT WELL LOCATION
2821 HWY 208, WELLINGTON, NV
Subdivision Name: County: LYON

2. LOCATION NE ¼ SW ¼ Sec 2 T 10N N/S R 23 E
PERMIT/WAIVER No. 71948 (issued by Water Resources) 010-641-06 Parcel No.

Latitude
Longitude
UTM E 11S0293354 ☐ NAD 27
N 4292352 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND & GRAVEL	80	0	100	100
COARSE SAND		100	120	20
SAND	XXX	120	140	20
[redacted]				
WELDED A 2" PORT AT TOP				
OF CASING AS PER STATE				
N 38.755789				
W 119.377150 NAD27				

Date started: 17-Jan , 20 07
Date completed: 29-Jan , 20 07

9. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 140 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	140	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	.188	+1	140

Perforations:
Type of perforation MACHINE MILL SLOT
Size of perforation 1/8" X 3"
From 120 feet to 140 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 100 ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type: NATIVE MATERIAL IN THE HOLE
Bentonite Chips: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 65 feet below land surface
Artesian Flow: NO G.P.M. P.S.I.
Water Temperature: 80 °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AIR LIFT	60		2

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1408
Signed (By driller performing actual drilling on site or contractor)
Date 2/2/2007

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY