WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102833
Permit No.
Basin 154

NOTICE OF INTENT NO. 51413

1. OWNER Stephen Bruner
MAILING ADDRESS POB 1003
McGill, NV 89315

ADDRESS AT WELL LOCATION 11 Miles North on Hwy. 892, Newark Valley

2. LOCATION SE ¼ SE ¼ Sec. 4 T. 19 N/S R. 55 E. White Pine County
PERMIT NO. (Issued by Water Resources) APN 09-090-02 (Parcel No.) N 39.539438 W 115.780051 NAD27 (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Oxidized Mill Tailings		0	20	20
Red Sand & Gravel		20	30	10
Limestone		30	65	35
Altered Limestone (Yellow)		65	75	10
Limestone		75	105	30
Altered Fractured L.S.		105	135	30
Limestone		135	150	15
Altered Limestone		150	210	60
Water Bearing Gravel	x	210	220	10
Sand & Gravel		220	245	25
Water Bearing Gravel	x	245	265	20
Lat. N39° 32' 21.7"	NAD83			
Longt. W115 46' 51.4"				
Elev. 6,038 ft.				

2007 FEB -5 AM 11:54 STATE ENGINEER'S OFFICE

Date started December 30, 20 06
Date completed January 18, 20 07

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
85	86	2

8. WELL CONSTRUCTION
Depth Drilled 265 Feet Depth Cased 265 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
10	0	265

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8"	12.92	.188	0	265

Perforations:
Type perforation Factory
Size perforation 1/8" x 2 1/2" 6 Rows
From 185 feet to 265 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 ft.
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 265 feet

9. WATER LEVEL
Static water level 174 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Christiansen Drilling, Inc. (Contractor)
Address 557 Ely Ave. (Contractor)
Ely, NV 89301
Nevada contractor's license number issued by the State Contractor's Board 14790
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1793
Signed Rick Lewis By Jerold D. Christiansen (By driller performing actual drilling on site or contractor)
Date January 31, 2007

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627