STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 103072
Permit No.
Basin 021

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59359

1. OWNER Darrel Coutts
MAILING ADDRESS PO Box 751

ADDRESS AT WELL LOCATION Ada Vista
Winnemucca, Nv 89445
Subdivision Name: County: Humboldt

2. LOCATION SE ¼SE¼ Sec33T36N/S R38E
Latitude N40°56'893" UTM E ☐ NAD 27
PERMIT/WAIVER NO. 10-681-05 Issued by Water Resources Parcel. No.
Longitude W117°42.035' N ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	5	5
Boulders		5	15	10
Cobles & Clay		15	75	60
Boulders		75	215	140
Clay Cobles		215	232	17
Hard Rock		232	245	13
Clay & Cobles		245	270	25
Boulder & Clay		270	300	30
Clay, Sand & Fine Gravel	X	300	330	30
Cobles		330	350	20

N 40.948328
W 117.699616 NAD27

Date started: 02/01, 20 07
Date completed: 02/07, 20 07

7. Water Level
Static water level: 263' feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: cool °F
Quality: Fair

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		5

9. WELL CONSTRUCTION
Depth Drilled 350 Feet Depth Cased 350 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	350	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	10	1.88	+1	350

Perforations:
Type of perforation Factory Cut
Size of perforation 3/32x4"
From 310 feet to 350 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 50 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 50 to 350 ☐ Pumped ☒ Poured
Type: 3/8"
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling, Inc. (CONTRACTOR)
Address 10760 S. Grass Valley Road (CONTRACTOR)
Winnemucca, Nv 89445
Nevada contractor's license number issued by the State Contractor's Board 21467
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2083
Signed Fred Anderson Drilling Inc
By driller performing actual drilling on site or contractor
Date 02/08/07

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com