

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY
Log No. 103499
Permit No.
Basin 051

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59814

1 OWNER Newmont Mining Corporation Incorporation
MAILING ADDRESS PO Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry
Subdivision Name: County: Eureka

2 LOCATION NW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E
PERMIT/WAIVER No. 610481 66938
Issued by Water Resources Parcel No.

Latitude UTM E 567118 [x] NAD 27
Longitude N 4514709 [] NAD 83/WGS 84

3 TYPE OF WELL
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

Is this well being plugged because a replacement well was drilled? No
Is there an existing well log? Yes
If yes, what is NDWR well log #? 71219

4 EXISTING WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [x] yes [] no
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	32	.30	+2	60

Was the well contaminated? [] yes [x] no
Was the casing pulled? [] yes [x] no
Was the casing over drilled? [] yes [x] no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used:

Existing Perforations:

Type of perforation	Full Flow Louvered
Size of perforation	0.125
From 60 feet to 400 feet	
From feet to feet	
From feet to feet	
From feet to feet	
From feet to feet	

Additional Perforations:

From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 301 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS
Material Used
From 0 feet to 400 feet abandonite [x] Pumped [] Poured
From 52 feet to 50 feet 3/8" hole plug [] Pumpe [x] Poured
From 52 feet to 0 feet neat cement [x] Pumped [] Poured
From feet to feet [] Pumped [] Poured
From feet to feet [] Pumped [] Poured
From feet to feet [] Pumped [] Poured

6 Additional Notes or Comments
Pumped 170 bags of abandonite slurry from bottom up until well was full. After abandonite subsided, poured bentonite to 52 ft pumped 7 bags neat cement from 52 to surface.
N 40.782534
W 116.204575 NAD27

Neat Cement Fluid Weight 15.8 lbs/gal
Bentonite Grout 12.5 % bentonite
Date Started 8/2/2007
Date Completed 8/2/2007

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Address PO Box 2748
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
Date 8/24/2007

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 05-06)