STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 103508
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 31425

1. OWNER Clark County Aviation
MAILING ADDRESS P.O. Box 11005
Las Vegas, Nv

ADDRESS AT WELL LOCATION McCarren Airport Terminal 3
5757 Wanye Newton Boulevard, Las Vegas, NV
Subdivision Name: County: Clark

2. LOCATION NW ¼ NW ¼ Sec 35 T 21S N/S R 61 E
PERMIT/WAIVER No. DW-1244A (Issued by Water Resources) 162-35-101-018 (Parcel No.)
Latitude Longitude
UTM E N NAD 27 x NAD 83/WGS 84
162-35-101-018

3. WORKED PERFORMED
New Well, Replace, Recondition, Deepen, x Other, Dewatering Well

4. PROPOSED USE ✓DEWATER
Domestic, Irrigation, Test, Municipal/Industrial, Monitor, Stock

5. WELL TYPE
Cable, Rotary, RVC, Air, x Other, Auger Bucket

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Well # 7421				
N486791.8 E633111.4				
Clayey Gravel		0	4	
Caliche - white/hard		4	8	
Fat Clay-with sand, gravel		8	18	
Silty Clayey Sand - red,brown		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	
Well #7422				
N486780.6 E633211.5				
Clayey Gravel		0	4	
Caliche - white/hard		4	8	
Fat Clay-with sand, gravel		8	18	
Caliche - white/hard		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	

Date started: 24-Jul, 20 07
Date completed: 24-Jul, 20 07

9. WELL CONSTRUCTION
Depth Drilled 51' Feet Depth Cased 50' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
24"	Inches	surface	Feet	51' BGL	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	3.6	.280	0	20

Perforations:
Type of perforation machine slot
Size of perforation .032"
From 20 feet to 50 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes X No
Neat Cement to Pumped Poured
Cement Grout to Pumped Poured
Concrete Grout to Pumped Poured
≥30% Bentonite Grout to Pumped Poured
Gravel Pack: X Yes No to Pumped X Poured
Type: pea gravel
Bentonite Chips: Yes X No to Pumped Poured
Type:

7. Water Level
Static water level: 26' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

DCNR/DWR
RECEIVED
AUG 03 2007
LAS VEGAS OFFICE

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Griffin Dewatering Corp (Contractor)
Address 536 E. Maitland Street (Contractor)
Ontario, Ca 91761
Nevada contractor's license number issued by the *State Contractor's Board* C-23 0031246
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2264
Signed (By driller performing actual drilling on site or contractor)
Date 7/31/07

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY