STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 103512
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

*Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 31425

1. OWNER Clark County Aviation
MAILING ADDRESS P.O. Box 11005
Las Vegas, Nv

ADDRESS AT WELL LOCATION McCarren Airport Terminal 3
5757 Wanye Newton Boulevard, Las Vegas, NV
Subdivision Name: County: Clark

2. LOCATION NW ¼ NW ¼ Sec 35 T 21S N/S R 61 E
PERMIT/WAIVER No. DW-1244A 162-35-101-018
Issued by Water Resources Parcel No. 162-35-101-018

Latitude
Longitude
UTM E NAD 27
N x NAD 83/WGS 84

3. WORKED PERFORMED
New Well, Replace, Recondition, Deepen, x Other, Dewatering Well

4. PROPOSED USE ✓DEWATER
Domestic, Irrigation, Test, Municipal/Industrial, Monitor, Stock

5. WELL TYPE
Cable, Rotary, RVC, Air, x Other, Auger Bucket

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Well # 7418 | | | | |
| N486852.3 E632810.8 | | | | |
| Clayey Gravel | | 0 | 11 | |
| Caliche - white/hard | | 11 | 13 | |
| Fat Clay-with sand, gravel | | 13 | 18 | |
| Silty Clayey Sand - red,brown | | 18 | 21 | |
| Clayey Gravel, cemented lenses | | 21 | 34 | |
| Sandy Fat Clay, brown to tan | | 34 | 47 | |
| Caliche - moderate cemented | | 47 | 49 | |
| Caliche - hard | | 49 | 51 | |

Date started: 6-Jul, 20 07
Date completed: 6-Jul, 20 07

9. WELL CONSTRUCTION
Depth Drilled 51' Feet Depth Cased 50' Feet

HOLE DIAMETER (BIT SIZE)
24" Inches From surface Feet To 50' BGL Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6.5 | 3.6 | .280 | 0 | 20 |
| | | | | |
| | | | | |

Perforations:
Type of perforation machine slot
Size of perforation .032"
From 20 feet to 50 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes X No
Neat Cement to Pumped Poured
Cement Grout to Pumped Poured
Concrete Grout to Pumped Poured
≥30% Bentonite Grout to Pumped Poured
Gravel Pack: X Yes No 0 50 Pumped X Poured
Type: pea gravel
Bentonite Chips: Yes X No to Pumped Poured
Type:

7. Water Level
Static water level: 26' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

DCNR/DWR
RECEIVED
AUG 03 2007

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Griffin Dewatering Corp (Contractor)
Address 536 E. Maitland Street (Contractor)
Ontario, Ca 91761
Nevada contractor's license number issued by the *State Contractor's Board* C-23 0031246
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2264
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 7/31/07

LAS VEGAS OFFICE