STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY	
Log No.	103526
Permit No.	
Basin	212

PRINT OR TYPE ONLY — DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 31424

1. OWNER: Clark County Aviation
MAILING ADDRESS: P.O. Box 11005, Las Vegas, Nv
ADDRESS AT WELL LOCATION: McCarren Airport Terminal 3, 5757 Wanye Newton Boulevard, Las Vegas, NV
Subdivision Name: County:

2. LOCATION: NE ¼ NE ¼ Sec 34 T 21 N/S R 61 E
Latitude: UTM E: NAD 27
Longitude: N: x NAD 83/WGS 84
PERMIT/WAIVER No.: DW-1243A (Issued by Water Resources) — Parcel No.: 162-34-502-010 / 162-35-101-018

3. WORKED PERFORMED: New Well; Replace; Recondition; Deepen x; Other: Dewatering Well

4. PROPOSED USE ✓ DEWATER: Domestic; Irrigation; Test; Municipal/Industrial; Monitor; Stock

5. WELL TYPE: Cable; Rotary; RVC; Air; x Other: Auger Bucket

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Well # 7460				
N486749.1 E631071.9				
Clayey Gravel		0	3	
Caliche - white/hard		3	7	
Fat Clay-with sand, gravel		7	18	
Silty Clayey Sand - red,brown		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	
Well #7401				
N486763.4 E631148.1				
Clayey Gravel		0	3	
Caliche - white/hard		3	7	
Fat Clay-with sand, gravel		7	18	
Silty Clayey Sand - red,brown		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	

Date started: 20-Jul, 20 07
Date completed: 7/20/2007, 20 07

7. Water Level
Static water level: 25' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: Bailer; x Pump; Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled: 51' Feet — Depth Cased: 50' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
24"	0	50
24" Inches	surface Feet	50' BGL Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	3.6	.280	0	20

Perforations:
Type of perforation: machine slot
Size of perforation: .032"
From 20 feet to 50 feet

Annular Seal: Yes; x No
Neat Cement; Cement Grout; Concrete Grout; ≥30% Bentonite Grout — to — Pumped — Poured
Gravel Pack: x Yes No 0 50 Pumped x Poured
Type: pea gravel
Bentonite Chips: Yes x No to Pumped Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor): Griffin Dewatering Corp
Address (Contractor): 536 E. Maitland Street, Ontario, Ca 91761
Nevada contractor's license number issued by the State Contractor's Board: C-23 0031246
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: M-2364
Signed: (By driller performing actual drilling on site or contractor)
Date: 7/31/07

DCNR/DWR RECEIVED AUG 03 2007

LAS VEGAS OFFICE