STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 103576
Permit No.
Basin 047

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60159

1. OWNER FASKIN OIL & RANCH LTD
MAILING ADDRESS 303 WEST WALL AVE, SUITE 1800
MIDLAND, TX 79701-5116

ADDRESS AT WELL LOCATION NOAH FEDERAL No. 1
47 26N 55E 22Cc
Subdivision Name: PARCEL OF LAND County: WHITE PINE

2. LOCATION NE ¼ SW ¼ Sec 32 T 26N N/S R 55 E
PERMIT/WAIVER No. OG-241 (Issued by Water Resources) 47 26N 55E 32Cc Parcel No.

Latitude 40.088640
Longitude 115.501575
UTM E 11T 0601913 [X] NAD 27
N 4438070 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[x] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [x] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOPSOIL		0	2	2
BOULDERS & SILTSTONE		2	6	4
RED CLAY		6	200	194
RED CLAY & GRAVEL MIX	240	200	260	60
BLACK ROCK		260	360	100
BLACK ROCK & SOME RED CLAY		360	400	40
RED SHALE		400	440	40

Date started: 14-Jul, 20 07
Date completed: 19-Jul, 20 07

9. WELL CONSTRUCTION
Depth Drilled 440 Feet Depth Cased 410 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 3/4	Inches	0	Feet	440	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	22.4	.250	+1.5	200
8 5/8	16.89	.188	200	410

Perforations:
Type of perforation MACHINED MILL SLOT
Size of perforation 3/16" X 3", DOUBLE ROW, 16 ROWS

From	230	feet to	270	feet
From	290	feet to	310	feet
From	370	feet to	390	feet
From		feet to		feet
From		feet to		feet

Annular Seal: [X] Yes [ ] No

[X] Neat Cement	0 to 100	[ ] Pumped	[X] Poured
[ ] Cement Grout	to	[ ] Pumped	[ ] Poured
[ ] Concrete Grout	to	[ ] Pumped	[ ] Poured
[ ] ≥30% Bentonite Grout	to	[ ] Pumped	[ ] Poured

Gravel Pack: [X] Yes [ ] No 110 to 410 [ ] Pumped [X] Poured
Type: 3/8" PEA GRAVEL
Bentonite Chips: [X] Yes [ ] No 100 to 110 [ ] Pumped [X] Poured
Type: 3'8" BENTONITE CHIPS

7. Water Level
Static water level: 160 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
80		5

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING INC
Contractor
Address P. O. BOX 850
Contractor
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1689
Signed
By driller performing actual drilling on site or contractor
Date 7/20/2007

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY