WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 103987
Permit No.
Basin 101

NOTICE OF INTENT NO. 57741

1. OWNER Fallon (NAS) Naval Air Station
MAILING ADDRESS 4755 Pasture Road Fallon NV 89496
ADDRESS AT WELL LOCATION 4755 Pasture Road Fallon NV 89496

2. LOCATION SW ¼ SE ¼ Sec. 23 T. 18 N/S R. 29 E. Churchill County
PERMIT NO. IRP (Issued by Water Resources) 006-611-01 (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. Sec 16 TT-MW-04 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
brown sandy silt		0	3	3
brown clayey silt		3	4	1
brown silt		4	5.5	1.5
brown silty sand	6'5"	5.5	7 3/4	2.25
brown clayey silt		7 3/4	8 3/4	1
brown silty sand		8 3/4	12.5	3.75
brown clayey silt		12.5	15	2.5
green-grey ~~clay~~/silty clay		15	20	5
N39.405448				
W 118.696427 NAD27				
* 8-14-07 3:40pm				
verbal waiver				
from Ryan Clark				
via Tamera (Tetra Tech)				
on gravel to 1' over screen				
on TT16-MW04 and				
TT16-MW05				
GPS N39°24.321'	WGS 84			
W118°41.840'				

Date started 8/15/2007, ~~19~~
Date completed 8/15/2007, ~~19~~

7. — WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 19.5 Feet Depth Cased 19 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	19.5 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		sch 40	+3	19

Perforations:
Type perforation slotted
Size perforation 0.010
From 4 feet to 19 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal (0 to 1.5) (bentonite 1.5'-3')
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 3 feet to 19.5 feet

9. WATER LEVEL
Static water level 6.5' feet below land surface
Artesian flow — G.P.M. P.S.I.
Water temperature WARM °F Quality MUCKY

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DALE LEHMAN (Contractor)
Address 520 Edison Way (Contractor)
Reno NV 89502
Nevada contractor's license number 0062596 issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1970
Signed Dale Lehman (By driller performing actual drilling on site or contractor)
Date 8/15/07

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627